# SAFETY DATA SHEET

Date of Issue: 01/01/2020



AEROCEL<sup>®</sup> SSPT<sup>™</sup>

Non-Continuous Tube with self-seal and protective rubber tape

# **1. PRODUCT AND COMPANY IDENTIFICATION**

Identification of Product:	Closed Cell Elastomeric Thermal Insulation sliced tube with self-sealing
	tape and protective rubber tube
Trade Name:	Aerocel <sup>®</sup> SSPT <sup>™</sup>
Manufacturer/Supplier:	Aeroflex USA, Inc.
	282 Industrial Park Road, Sweetwater, TN 37874
Telephone Number:	Toll Free 866-AEROCEL (237-6235)
Emergency Telephone Number:	ChemTel, Inc.
	1-800-255-3924 (North America)
	+1-813-248-0585 (International)

### 2. HAZARD IDENTIFICATION

#### Inhalation

No significant signs of any adverse health hazard are expected to occur as a result of inhalation exposure **Eye Contact** 

#### Eye Contact

No significant signs of any adverse health hazards are expected to occur as a result of eye contact

Ingestion

Practically non-toxic

#### **Skin Contact**

No Significant signs of any adverse health hazards are expected to occur as a result of skin contact

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### **Health Hazardous Components**

Elastomeric thermal insulation is an expanded, closed cell, cross-linked rubber compound. The rubber tape is a rubber type compound. They contain synthetic polymers, fillers, plasticizers and rubber chemicals. Since all of these material are bound in a polymer matrix, the product does not qualify as a hazardous material as defined by OSHA (29 CFR 1910.1200). Pressure sensitive coating is a synthetic rubber based ashesive wih a paper release liner and is classified as an article which is not hazardous as defined by OSHA (29 CFR 1910.1200).

#### Following are the main ingredients in this product:

### Rubber

Synthetic rubber (EPDM: Ethylene-Propylene-Terpolymer Rubber) CAS No. 25038-36-2 Aluminum Trihydrate CAS No. 21645-51-2 Carbon Black CAS No. 1333-86-4

#### Pressure Sensitive Adhesive

Copolymers of acrylic acid, methacrylic acid, ester of these acid CAS No. 90011-14-7

# SAFETY DATA SHEET

Date of Issue: 01/01/2020



# AEROCEL<sup>®</sup> SSPT™

Non-Continuous Tube with self-seal and protective rubber tape

4. FIRST AID MEASURES	
Inhalation	Not required under normal use. If irritation persists, remove from exposure area
Eye Contact	No required under normal use. Flush with water until all traces of the material are done.
	Seek medical attention if irritation persists
Ingestion	If illness or adverse symptoms develop, obtain medical attention
Skin Contact	Not required under normal use

### 5. FIRE-FIGHTING MEASURES

### Extinguishing Media

Carbon Dioxide, ABC dry chemical, Water spray and foam

#### Specific Hazards with regard to Fire-Fighting measures

Approach from upwind side. Avoid breathing smoke, fumes or vapors on downwind side.

Firefighters wear protective clothing, especially eye protection, and self contained breathing apparatus

# **Hazardous Combustion Products**

Material is stable under normal conditions. In the event of a prolonged fire, may generate Carbon Monoxide, Carbon Dioxide, Low molecular weight alcohol/aldehydes and acid.

### 6. ACCIDENTAL RELEASE MEASURES

### If materials released/Spill

 Land Spill
 Collect spilled material and place it in an appropriate container for reuse or disposal

 Water Spill
 Product is insoluble. Collect spilled material and place in an appropriate container

 for reuse or disposal
 Neutralizing Agent

#### 7. HANDLING AND STORAGE

Handling ConditionNo special precaution requiredStorage ConditionKeep in dry normal storage

## 8. EXPOSURE CONTROL/PERSONAL PROTECTION

Engineering Controls Personal Protection General ventilation Negligible

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Expanded Foam Rubber
Specific Gravity (H <sub>2</sub> O=1)	0.04-0.06
Service Temperature	-297°F to 257°F (-182°C to +125°C)
Thermal Conductivity	0.245 BTU.in/ft <sup>2</sup> .hr.°F at Mean temp 75°F

# SAFETY DATA SHEET

Date of Issue: 01/01/2020



### **AEROCEL<sup>®</sup> SSPT™**

Non-Continuous Tube with self-seal and protective rubber tape

# 9. PHYSICAL AND CHEMICAL PROPERTIES (Cont.)

Water Absorption Water Vapor Permeability Weather and UV resistance Flammability 0.2% by volume Max 0.03 Perm-inch (4.35 x 10<sup>-11</sup> g/Pa.m.s) Minimal Cracking Self-extinguishing

### **10. STABILITY AND REACTIVITY**

Stability and Reaction	Stable
Conditions to avoid	Negligible
Hazardous Decomposition Product	May generate Carbon Monoxide, Carbon Dioxide,
	Low molecular weight alcohol/aldehydes and acid
Hazardous Polymerization	Will not occur

# **11. TOXICOLOGICAL INFORMATION**

No Data

### **12. ECOLOGICAL INFORMATION**

No Data

# **13. DISPOSAL CONSIDERATION**

Waste material may be disposed of in an approved landfill or may be incinerated under conditions which meet federal, state, and local environmental regulation.

#### **14. TRANSPORT INFORMATION**

No Data

# **15. REGULATORY INFORMATION**

No Data

### **16. OTHER INFORMATION**

The information supplied herein is related to material specified and may not be valid if used in combination with other material or process. Further the information contained here is believed to be reliable and based on correct state of our knowledge. However no guarantees of any kind can be give as to its accuracy.