

Johns Manville Zeston® PVC Fitting Sizes for AEROFLEX EPDM™ Pipe Insulation

AEROFLEX	INSULATION THICKNESS						
	1/4"	3/8"	1/2"	3/4"	1"	1-1/2"	2"
Label ID	PVC Size	PVC Size	PVC Size	PVC Size	PVC Size	PVC Size	PVC Size
1/4"	N/A	N/A	N/A	3	5	9	N/A
3/8"	N/A	N/A	2	3	6	9	12
1/2"	N/A	N/A	2	4	6	10	12
5/8"	N/A	2	3	5	7	10	12
3/4"	N/A	2	3	5	7	10	12
7/8"	2	3	4	6	8	11	13
1-1/8"	3	4	5	7	9	11	13
1-3/8"	N/A	5	6	8	10	12	14
1-5/8"	N/A	6	7	9	10	12	15
1-7/8"	N/A	7	8	10	11	13	15
2-1/8"	N/A	8	9	10	11	13	15
2-3/8"	N/A	9	10	11	11	14	16
2-5/8"	N/A	10	10	11	12	14	16
2-7/8"	N/A	10	11	12	13	15	17
3-1/8"	N/A	11	11	12	13	15	17
3-1/2"	N/A	11	12	13	14	16	18
3-5/8"	N/A	12	12	13	14	16	18
4-1/8"	N/A	13	13	14	15	17	18
4-1/2"	N/A	13	14	15	16	18	19
5-1/8"	N/A	N/A	15	16	17	18	19
5-1/2"	N/A	N/A	16	17	18	19	20
6-1/8"	N/A	N/A	17	18	18	19	21
6-5/8"	N/A	N/A	18	18	19	20	21
8-5/8"	N/A	N/A	20	20	21	22	22
10-3/4"	N/A	N/A	22	22	22	24	25
12-3/4"	N/A	N/A	N/A	N/A	24	26	27
14"	N/A	N/A	N/A	N/A	26	27	28
16"	N/A	N/A	N/A	N/A	28	29	30*

WARNING:

Revised 112525

* Fitting size #30 - only 45° and short-radius 90° elbows available - no tees or valves.

- AEROFLEX EPDM™ pipe OD's are larger than fiberglass; recommended PVC fitting sizes in chart may be larger than for the same fiberglass pipe size.
- Outside diameters calculated using maximum ID and wall thickness tolerance per ASTM C534 Type I; actual OD may be smaller.
- This table is provided as a convenience for sizing jacketing materials. It is ultimately the responsibility of the installer to determine the correct fit of jacketing materials over AEROFLEX EPDM pipe insulation.