



# AEROFLEX®

Protective/Decorative Coating for EPDM Insulation



## Aerocoat LVOC®

Low-VOC Coating for  
AEROFLEX EPDM™ Insulation





# Aerocoat LVOC<sup>®</sup>

**Low-VOC content and emissions**  
**Best choice for LEED<sup>®</sup> and Living Building Challenge (LBC) projects**

HVAC | Refrigeration | VRF | Chilled Water Ductwrap | Hot & Cold-Water Piping

Low-VOC, water-based coating for AEROFLEX EPDM<sup>™</sup> insulation. Provides a decorative finish on interior installations, adds UV protection and code compliance for exterior applications.

*U.S. energy codes require mandatory shielding of cellular pipe insulation in exterior environments. Coatings such as Aerocoat LVOC are compliant; adhesive tapes alone are not.*

Sizes: 1-gallon containers (White)

## Fast, simple to install

Ready to apply right out of the container (no diluting or tinting recommended)

Two coats required to achieve 100% coverage

## Superior performance

Protects AEROFLEX EPDM<sup>™</sup> insulation from environmental factors such as solar radiation, moisture, wind, equipment maintenance

UV and water-retardant

Designed to expand and contract with insulation

Prolongs life expectancy of AEROFLEX EPDM<sup>™</sup> insulation

## Safe for indoor & outdoor environments


Low-VOC content and emissions

MAS Certified Green<sup>®</sup>

Complies with LEED<sup>®</sup> VOC requirements for interior-applied and exterior-applied coatings

Does not contain LBC Red List chemicals

## AEROFLEX EPDM<sup>™</sup> insulation system solutions



### Aerofix<sup>®</sup>

Light-weight, rigid pipe supports, pre-insulated with high-density, load-bearing foam and encased with zero-perm EPDM polymer membrane. Includes built-in pressure sensitive Protape<sup>®</sup> closure system.



### AeroFit<sup>™</sup>

Pre-fabricated insulation fittings made of AEROFLEX EPDM<sup>™</sup> rubber for high-quality installation on HVAC and plumbing piping.



Courtesy of Nelson Insulation Company

### Protape<sup>®</sup>

Zero-perm EPDM-based, self-adhering rubber tape for sealing glued insulation seams and termination points.



### AEROFLEX<sup>®</sup> Adhesives

Specially formulated adhesives for bonding and vapor-sealing AEROFLEX<sup>®</sup> EPDM insulation. Fast tack and LVOC formulations available.

**Product:** White, low-VOC, water-based coating specially formulated to protect AEROFLEX EPDM™ insulation for interior and exterior applications.

**Installation Instructions:**



**Application:** If AEROFLEX Aeroseal or Aeroseal LVOC™ Black adhesive was dry to the touch prior to contact, Aerocoat LVOC may be applied immediately after installation. For AEROFLEX REF 1520™ adhesive, refer to data sheet for required dry times. Before applying make sure insulation surfaces are clean and free from oil, grease, dust or loose portions of any previous coating. Stir Aerocoat LVOC thoroughly and apply with brush or roller to the clean surface. No primer is required. Apply 2 coats allowing a minimum of 4 hours drying time (75°F, 70% RH) before applying second coat. Dilution or tinting of coating is not recommended due to negative impact on product performance. Recommended application ambient temperature is 50°F to 100°F (10°C to 38°C). Full cure time is 24 hours.

**Read all warnings on product label before use.**

**Clean Up:** Clean Water

**Physical Properties**

Composition	Water-based
Solids Content	Approximately 55% by weight
Net Weight	11 lbs/gal
Appearance	Low-Gloss
VOC	Content < 50 g/L, Emissions < 0.5 mg/m3
Red List Chemicals	Zero
Fungi Resistance	Excellent
Flammability	Nonflammable
Coverage	Up to 300 ft2/gal
Application	Brush or roller
Dry Time	Minimum of 4 hours between coats (75°F, 70% RH)
Reapply	3-5 years
Storage	60°F to 80°F (16°C to 27°C), protect from freezing
Shelf Life	1 year (date of purchase)

**Additional Approvals, Compliances, Etc.**

ANSI/ASHRAE/IES Standard 90.1	Energy Standard for Buildings Except Low-Rise Residential Buildings
BABA	Buy America, Build America Act
Buy American	Buy American, Federal Acquisition Regulation, FAR 52.225 Buy American
IECC®	International Energy Conservation Code®
CA Title 24	California Building Energy Efficiency Standards
California Specification 01350	VOC Emissions, Standard Method v1.2
SCAQMD Rule 1113	Architectural Coatings, LEED® for Healthcare and Schools
Materials Red List	International Living Future Institute (ILFI) Living Building Challenge (LBC) standard

**Potential LEED® Credit Contributions**

Indoor Environmental Quality (EQ)	Credit: Low-Emitting Materials, Interior and Exterior-Applied Coatings
-----------------------------------	--





**Aeroflex USA**  
Sweetwater, TN  
[www.aeroflexusa.com](http://www.aeroflexusa.com)

061926